

In-stock Proax Power Supply Program

Same-day
Shipping!

Essential 2

The ESSENTIAL POWER range is an ideal choice for systems with basic energy requirements. It meets basic industry standards for worldwide use at a cost-sensitive price.

Family	Input	Output	Amps	Dimension (L x H x W in mm)	Part #	Description
Essential 2	100 V AC ... 240 V AC	24 V DC	2.5A	33 x 90 x 100	1394764	PS-EE-2G/1AC/24DC/60W/SC
			3A	40 x 124 x 125	1234301	PS-EE-2G/1AC/24DC/75W/SC
			5A		1234302	PS-EE-2G/1AC/24DC/120W/SC
			10A		1234304	PS-EE-2G/1AC/24DC/240W/SC
			20A	86 x 124 x 125	1234308	PS-EE-2G/1AC/24DC/480W/SC



Uno & Uno2

Thanks to their high power density, UNO POWER power supplies, with basic functionality, are ideal for to use in compact control cabinets. Due to their high output and low no-load losses, they achieve high energy efficiency. Extended temperature range from -25°C to +70°C (device start-up at -40°C)

Family	Input	Output	Amps	Dimension (L x H x W in mm)	Part #	Description
Uno & Uno2	85 V AC ... 264 V AC	24 V DC	1.3A	22.5 x 90 x 84	2902991	UNO-PS/1AC/24DC/ 30W
			2.5A	35 x 90 x 84	2902992	UNO-PS/1AC/24DC/ 60W
			4.2A	55 x 90 x 84	2902993	UNO-PS/1AC/24DC/100W
			5A	35 x 130 x 129	1110466	UNO2-PS/1AC/24DC/120W
			10A	45 x 130 x 129	1096432	UNO2-PS/1AC/24DC/240W
			20A	59 x 130 x 129	2910105	UNO2-PS/1AC/24DC/480W
			40A	126 x 130 x 129	1110043	UNO2-PS/1AC/24DC/960W



TRIO3

The NEW TRIO3 is a robust, flexible power supply module available in two versions for your control cabinets:

- Standard power supply module for reliable 24 V voltage and output currents from 5 to 40 A
- Power supply module with integrated multi-channel circuit breaker and IOLINK
- Extended temperature range from -25°C to +70°C (unit starts up at -40°C)
- Dynamic increase of up to 150% for 5 seconds

Family	Input	Output	Amps	Dimension (L x H x W in mm)	Part #	Description
TRIO3	85 V AC ... 264 V AC	24 V DC	5A	35 x 135 x 120	1159037	TRIO3-PS/1AC/24DC/5
			10A	40 x 135 x 132	1159038	TRIO3-PS/1AC/24DC/10
			20A	55 x 135 x 132	1159039	TRIO3-PS/1AC/24DC/20
	10A		40 x 135 x 132	1159042	TRIO3-PS/3AC/24DC/10	
	20A		60 x 135 x 132	1159044	TRIO3-PS/3AC/24DC/20	
	40A		90 x 135 x 167	1159045	TRIO3-PS/3AC/24DC/40	
	3 Phases 3 x 320VAC ... 550VAC	IO Link version with integrated electronic circuit breakers				
		24 V DC	10A	68 x 135 x 132	1252696	TRIO3-PS/1AC/24DC/10/4C/IOL
			20A	88 x 135 x 132	1252697	TRIO3-PS/1AC/24DC/20/8C/IOL



QUINT4

QUINT POWER high-performance power supplies with advanced features offer you maximum system availability through SFB Technology and individual configuration of signal thresholds and characteristic curves.

Family	Input	Output	Amps	Dimension (L x H x W in mm)	Part #	Description
QUINT4	85 V AC ... 264 V AC 90 V DC ... 350 V DC	24 V DC	5A	36 x 130 x 125	2904600	QUINT4-PS/1AC/24DC/5
			10A	50 x 130 x 125	2904601	QUINT4-PS/1AC/24DC/10
			20A	70 x 130 x 125	2904602	QUINT4-PS/1AC/24DC/20
			40A	120 x 130 x 125	2904603	QUINT4-PS/1AC/24DC/40



Shop Now

WeAutomate

proax.ca